

**Product Information Sheet:**

Date: 01/10/2012

Ref: AP/PXE/01

---

# AGCO Parts Premium Extra Engine Oil 15W-40

## AGCO Parts references:

---

VACC3609 20ltr  
VACC3610 205ltr  
VACC3611 1000ltr  
VACC3612 Bulk

## Applications

---

Premium Extra Engine Oil 15W-40 is a low SAPS (Sulphated Ash, Phosphorus and Sulphur) heavy duty diesel engine oil that has been formulated for use where exhaust after-treatment devices have been employed to reduce emissions. This product may be used to provide high levels of protection in Tier 4 and Stage 3B engines, operating in very severe conditions, including temperatures down to -20°C\*.

Premium Extra Engine Oil 15W-40 has been developed for use in engines filtered with particulate filters (DPFs), SCR NOX and EGR reduction systems.

\*Please seek technical advice for operating temperatures below -20°C.

## Main Benefits

---

- After-treatment device compatible
- Outstanding Soot Handling
- Enhanced Sludge Dispersion
- High levels of Piston Cleanliness
- Improved Anti-wear protection

## Specifications

---

API CJ -4 / SM  
ACEA E9 - 08  
CAT ECF-3  
Cummins CES 20081  
MAN M3275  
Mack EO-O Premium Plus  
DDC PGOS 93 IT 218  
EMA DHD -1  
Mercedes Benz 228.31  
Volvo VDS-4  
Renault VI RDL-3 Compliance

## Storage

---

All packages should be stored under cover. Where outside storage is unavoidable drums should be laid horizontally to avoid the possible ingress of water and the obliteration of drum markings. Products should not be stored above 60°C, exposed to hot sun or freezing conditions.

## Health, Safety and Environment

---

Health, safety and environmental information is provided for this product in the Materials Safety Data Sheet. This gives details of potential hazards, precautions and First Aid measures, together with environmental effects and disposal of used products.

You should ensure that the product is only used for the purpose specified.

## Typical Characteristics

---

<b>SAE Classification</b>	<b>15W-40</b>
Density @ 15°C	0.875
Kinematic Viscosity at 100°C, cSt.	14.4
Kinematic Viscosity at 40°C, cSt.	96
Viscosity Index	155
Flash Point (closed) °C	180
Sulphated Ash %Wt.	1.0
TBN	7.06
Pour Point, °C	-35

The above figures are typical of those obtained with normal production tolerance and do not constitute a specification.

This Product Information Sheet contains details considered to be accurate at the date of printing. No warranty or representation, expressed or implied, is made as to the accuracy or completeness of the data and information contained in this publication.

The Seller shall not be responsible for any loss or damage resulting from any hazards or risks identified in the data sheet and which are associated with petroleum products concerned (provided that this disclaimer shall not affect any statutory rights of the Buyer of the petroleum products concerned).

It is the User's obligation to evaluate and use products safely and within the scope advised in the data sheet and to comply with all applicable laws and regulations. No statement made in this publication shall be construed as a permission, recommendation or authorisation given or implied to practice any patented invention without a valid licence.

You should always refer to the relevant machine Operators Instruction Manual and only use correct specifications advised