

Revision Date 14/05/2015
Revision 8
Supersedes date 16/03/2015



SAFETY DATA SHEET

AGCO Parts LHM Extra

SECTION 1: IDENTIFICATION OF THE SUBSTANCE/MIXTURE AND OF THE COMPANY/UNDERTAKING

1.1. Product identifier

Product name	AGCO Parts LHM Extra
Product No.	7555-178
Internal Id	11151
REACH Registration number	n/a Mixture

1.2. Relevant identified uses of the substance or mixture and uses advised against

Identified uses	Suspension and Hydraulic Fluid
-----------------	--------------------------------

1.3. Details of the supplier of the safety data sheet

Supplier	Oil Distributors 2a South Belt Rangiora 7400 Ph: 0800 70 10 10 Fax: 03 313 6428 admin@oildistributors.co.nz
----------	---

1.4. Emergency telephone number

National Poison Control Centre 0800 764 766

SECTION 2: HAZARDS IDENTIFICATION

2.1. Classification of the substance or mixture

Classification (EC 1272/2008)

Physical and Chemical Hazards Not classified.
Human health Asp. Tox. 1 - H304 Environment Not classified.

Classification (1999/45/EEC) Not classified.

The Full Text for all R-Phrases and Hazard Statements are Displayed in Section 16.

2.2. Label elements

Label In Accordance With (EC) No. 1272/2008

AGCO Parts LHM Extra



Signal Word	Danger	
Hazard Statements	H304	May be fatal if swallowed and enters airways.
Precautionary Statements	P261	Avoid breathing dust/fume/gas/mist/vapours/spray.
	P301+310	IF SWALLOWED: Immediately call a POISON CENTER or doctor/physician.
	P331	Do NOT induce vomiting.
	P501 a	Dispose of contents/container to hazardous or special waste collection point.
Supplementary Precautionary Statements	P405	Store locked up.

2.3. Other hazards

This product does not contain any PBT or vPvB substances.

SECTION 3: COMPOSITION/INFORMATION ON INGREDIENTS

3.2. Mixtures

Lubricating Oil (Petroleum) C15-30 hydrotreated neutral oil-based	60-100%
CAS-No.: 72623-86-0	EC No.: 276-737-9
	Registration Number: 01-2119474878-16
Classification (EC 1272/2008) Asp. Tox. 1 - H304	Classification (67/548/EEC) Not classified.
Hydroseal G232H	10-30%
CAS-No.: 64742-46-7	EC No.: 265-148-2
	Registration Number: 01-2119826592-36
Classification (EC 1272/2008) Asp. Tox. 1 - H304	Classification (67/548/EEC) Xn;R65.
Ethyl 3-[[bis(1-methylethoxy)phosphinothioy]thio]propionate	< 1%
CAS-No.: 71735-74-5	EC No.: 275-965-6
Classification (EC 1272/2008) Aquatic Chronic 2 - H411	Classification (67/548/EEC) N;R51/53.

The Full Text for all R-Phrases and Hazard Statements are Displayed in Section 16.

REACH Registration number n/a Mixture

AGCO Parts LHM Extra

Ingredient notes

Complex mixture of performance additives in an oil base. A petroleum product. DMSO extract < 3 % weight (IP 346)

Composition Comments

The data shown are in accordance with the latest EC Directives.

SECTION 4: FIRST AID MEASURES

4.1. Description of first aid measures

General information

Get medical attention if any discomfort continues.

Inhalation

In case of inhalation of spray mist: Move person into fresh air and keep at rest. Get medical attention if any discomfort continues.

Ingestion

Get medical attention if any discomfort continues. Do not induce vomiting.

Skin contact

Remove contaminated clothing immediately and wash skin with soap and water.

Eye contact

Immediately flush with plenty of water for up to 15 minutes. Remove any contact lenses and open eyes wide apart. Get medical attention promptly if symptoms occur after washing.

4.2. Most important symptoms and effects, both acute and delayed

General information

If aspiration into the lungs is suspected, eg when vomiting, admit to hospital immediately.

Inhalation

Upper respiratory irritation.

Ingestion

May cause discomfort if swallowed. The product contains mineral oil, which if aspirated into the lungs through vomiting after ingestion, may result in chemical pneumonia. Skin contact

Prolonged contact may cause redness, irritation and dry skin.

Eye contact

Irritation of eyes and mucous membranes.

4.3. Indication of any immediate medical attention and special treatment needed

Treat Symptomatically.

SECTION 5: FIREFIGHTING MEASURES

5.1. Extinguishing media

Extinguishing media

Extinguish with foam, carbon dioxide, dry powder or water fog.

Unsuitable extinguishing media

Do not use water jet as an extinguisher, as this will spread the fire.

5.2. Special hazards arising from the substance or mixture

Hazardous combustion products

In case of fire, toxic gases (CO, CO₂, NO_x) may be formed. Fire may also create other unidentified organic gases some of which may be toxic.

Unusual Fire & Explosion Hazards

AGCO Parts LHM Extra

Heat from fire could result in drums bursting

5.3. Advice for firefighters

Special Fire Fighting Procedures

Keep run-off water out of sewers and water sources. Dike for water control.

Protective equipment for fire-fighters Self-contained breathing apparatus.

SECTION 6: ACCIDENTAL RELEASE MEASURES

6.1. Personal precautions, protective equipment and emergency procedures

For personal protection, see section 8. In case of spills, beware of slippery floors and surfaces.

6.2. Environmental precautions

Contain spillage with sand or earth. Do not allow to enter drains, sewers or watercourses. The product is insoluble in water and will spread on the water surface.

6.3. Methods and material for containment and cleaning up

Contain spillage with sand or earth. Use sealed containers for reclamation or dispose of at a licenced hazardous waste collection point. Avoid contact with water. Spillages or uncontrolled discharges into watercourses must be IMMEDIATELY alerted to the Environmental Agency or other appropriate regulatory body. In case of spillage on water prevent the spread by use of suitable barrier equipment

6.4. Reference to other sections

For personal protection, see section 8. See section 11 for additional information on health hazards. For waste disposal, see section 13.

SECTION 7: HANDLING AND STORAGE

7.1. Precautions for safe handling

Avoid spilling, skin and eye contact. Always remove oil with soap and water or skin cleaning agent, never use organic solvents. Do not use oil-contaminated clothing or shoes, and do not put rags moistened with oil into pockets.

7.2. Conditions for safe storage, including any incompatibilities

Store in tightly closed original container in a dry, cool and well-ventilated place.

Storage Class

Miscellaneous hazardous material storage.

7.3. Specific end use(s)

The identified uses for this product are detailed in Section 1.2.

SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION

8.1. Control parameters

Name	STD	TWA - 8 Hrs		STEL - 15 Min		Notes
Hydroseal G232H	WEL		5 mg/m ³			
Lubricating Oil (Petroleum) C15-30 hydrotreated neutral oil-based	ACGIH		5 mg/m ³			

WEL = Workplace Exposure Limit.

ACGIH = American Conference of Governmental Industrial Hygienists.

AGCO Parts LHM Extra

8.2. Exposure controls

Protective equipment



Process conditions

Use engineering controls to reduce air contamination to permissible exposure level.

Engineering measures

Provide adequate ventilation, including appropriate local extraction, to ensure that the defined occupational exposure limit is not exceeded.

Respiratory equipment

No specific recommendation made, but respiratory protection must be used if the general level exceeds the recommended occupational exposure limit. Hand protection

The most suitable glove must be chosen in consultation with the gloves supplier, who can inform about the breakthrough time of the glove material.

Eye protection

If risk of splashing, wear safety goggles or face shield.

Other Protection

Use barrier creams to prevent skin contact.

Hygiene measures

Wash promptly with soap & water if skin becomes contaminated.

Thermal hazards

Not anticipated under normal conditions of use. The product is combustible if heated excessively and an ignition source is applied.

Environmental Exposure Controls

Do not allow product to contaminate land.

SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES

9.1. Information on basic physical and chemical properties

Appearance	Liquid
Colour	Green.
Odour	Characteristic. Oil smell.
Solubility	Insoluble in water Soluble in: Organic solvents.
Initial boiling point and boiling range (°C)	IBP >270C
Melting point (°C)	Not applicable. Pour Point < -50C
Relative density	0.845 @ 15C
Vapour density (air=1)	>1 Air = 1
Vapour pressure	<0.1 kPa @ 20C
Evaporation rate	< 1 n-butyl acetate =1
Viscosity	19 cSt @ 40C Not water soluble.

AGCO Parts LHM Extra

Decomposition temperature (°C)	Not determined. > 200 C
Flash point (°C)	>120C PM Closed cup.
Auto Ignition Temperature (°C)	Not determined
Flammability Limit - Lower(%)	Not known.
Flammability Limit - Upper(%)	Not known.
Partition Coefficient (N-Octanol/Water)	Not determined. log Kow > 6

The above figure is typical of mineral oil. The product is a complex mixture and differing components will have greater or lesser affinities for various solvents.

Explosive properties

This product is not considered explosive.

Other Flammability

Product is not classified as flammable but is combustible.

Material is considered non-oxidizing.

9.2. Other information

Volatility Description	Not considered volatile. Vapours may be emitted on excessive heating. The product is a complex mixture, the majority of which would not be classed as a VOC. However it cannot be discounted that trace or low levels of VOC's may be present.
------------------------	---

SECTION 10: STABILITY AND REACTIVITY

10.1. Reactivity

No specific reactivity hazards associated with this product.

10.2. Chemical stability

Stable under normal temperature conditions and recommended use.

10.3. Possibility of hazardous reactions

Unlikely to occur under normal conditions of use.

Hazardous Polymerisation

Unlikely to occur.

10.4. Conditions to avoid

Avoid heat, flames and other sources of ignition.

10.5. Incompatible materials

Materials To Avoid

Strong oxidising substances.

10.6. Hazardous decomposition products

Thermal decomposition or combustion may liberate carbon oxides and other toxic gases or vapours.

SECTION 11: TOXICOLOGICAL INFORMATION

11.1. Information on toxicological effects

Acute toxicity:

AGCO Parts LHM Extra

Acute Toxicity (Oral LD50)

> 2000 mg/kg Rat

Based on available data the classification criteria are not met. Data is based on information on components and knowledge and experience of this and similar product types.

Acute Toxicity (Dermal LD50)

> 2000 mg/kg Rabbit

Based on available data the classification criteria are not met. Data is based on information on components and knowledge and experience of this and similar product types. Acute Toxicity (Inhalation LC50)

Not determined.

Not expected to be highly toxic based on information of ingredients.

Skin Corrosion/Irritation:

Based on available data the classification criteria are not met. Slightly irritating.

The classification criteria are not met. May cause mild skin irritation. Prolonged or repeated skin contact eg. from clothing wet with lubricant may cause dermatitis. Symptoms may include redness, edema, drying, and cracking skin.

Serious eye damage/irritation:

May cause mild, short lasting discomfort to eyes. Based on available data the classification criteria are not met.

Respiratory or skin sensitisation:

The product is unlikely to present any significant inhalation hazard at ambient temperatures and under normal conditions of use.

Repeated exposure to oil mists may cause respiratory damage.

Not expected to be a skin sensitizer based on information on components.

Carcinogenicity:

This product contains mineral oils which are considered to be severely refined and not considered to be carcinogenic under IARC. All of the oils in this product have been demonstrated to contain less than 3% extractables by the IP346 test

Reproductive Toxicity:

No data available to suggest the product will cause reproductive toxicity.

Aspiration hazard:

Viscosity

Kinematic viscosity $\leq 20.5 \text{ mm}^2/\text{s}$.

Product may be considered an aspiration hazard under CLP regulations.

General information

This product has low toxicity. Only large volumes may have adverse impact on human health.

Inhalation

Unlikely to be hazardous by inhalation because of the low vapour pressure of the substance at ambient temperature.

Ingestion

No harmful effects expected in amounts likely to be ingested by accident.

Skin contact

Skin irritation is not anticipated when used normally. Repeated exposure may cause skin dryness or cracking.

Eye contact

AGCO Parts LHM Extra

May cause temporary eye irritation.

Specific effects

Prolonged or repeated contact with used oil may cause serious skin diseases, such as dermatitis and skin cancer.

SECTION 12: ECOLOGICAL INFORMATION

Ecotoxicity

The product is not classed as 'Dangerous to the Environment' but this does not exclude the possibility that large spills may have a damaging effect on the environment. The product contains substances which are toxic to aquatic organisms and which may cause long term adverse effects in the aquatic environment.

12.1. Toxicity

Acute Fish Toxicity

The classification criteria are not met.

Not expected to be highly toxic to fish. Based on available data the classification criteria are not met. Data based on information on components and knowledge and experience of similar product types.

Not expected to be highly toxic to aquatic invertebrates. Based on available data the classification criteria are not met. Data based on information on components and knowledge and experience of similar product types.

12.2. Persistence and degradability

The product contains mineral oil which has limited biodegradability in CEC test methods but will biodegrade slowly in aerobic water and sediments and is considered ultimately biodegradable. Degradability

The product is not readily biodegradable.

The product is based on highly refined mineral oils that are considered stable to hydrolysis.

The product is considered stable in the presence of water.

Biodegradation

Not determined.

The product is not considered readily biodegradable, albeit the major constituents are expected to ultimately biodegrade.

Inherently biodegradable Based on knowledge of ingredients.

Biological Oxygen Demand

Not determined. Chemical

Oxygen Demand Not

determined.

12.3. Bioaccumulative potential

Bioaccumulative potential

Bioaccumulation is unlikely to be significant because of the low water solubility of this product.

Bioaccumulation factor

Not determined.

Partition coefficient

Not determined.

log Kow > 6

The above figure is typical of mineral oil. The product is a complex mixture and differing components will have greater or lesser affinities for various solvents. 12.4. Mobility in soil

Mobility:

The product is non-volatile. The product is insoluble in water and will spread on the water surface.

Henry's Law Constant Not determined.

12.5. Results of PBT and vPvB assessment

Information is not available at this time.

AGCO Parts LHM Extra

Statutory Instruments

The Chemicals (Hazard Information and Packaging for Supply) Regulations 2009 (S.I. 2009 No. 716).

Approved Code Of Practice

Safety Data Sheets for Substances and Preparations.

Guidance Notes

Workplace Exposure Limits EH40.

EU Legislation

Dangerous Preparations Directive 1999/45/EC. Dangerous Substance Directive 67/548/EEC. Regulation (EC) No 1907/2006 of the European Parliament and of the Council of 18 December 2006 concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals (REACH), establishing a European Chemicals Agency, amending Directive 1999/45/EC and repealing Council Regulation (EEC) No 793/93 and Commission Regulation (EC) No 1488/94 as well as Council Directive 76/769/EEC and Commission Directives 91/155/EEC, 93/67/EEC, 93/105/EC and 2000/21/EC, including amendments. Regulation (EC) No 1272/2008 of the European Parliament and of the Council of 16 December 2008 on classification, labelling and packaging of substances and mixtures, amending and repealing Directives 67/548/EEC and 1999/45/EC, and amending Regulation (EC) No 1907/2006 with amendments.

15.2. Chemical Safety Assessment

No chemical safety assessment has been carried out.

ERMA Approval Code: HSR002606

SECTION 16: OTHER INFORMATION

Revision Comments

NOTE: Lines within the margin indicate significant changes from the previous revision.

Revision Date 14/05/2015

Revision 8

Supersedes date 16/03/2015

Risk Phrases In Full

R65 Harmful: may cause lung damage if swallowed.

NC Not classified.

R51/53 Toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment.

Hazard Statements In Full

H304 May be fatal if swallowed and enters airways.

H411 Toxic to aquatic life with long lasting effects.

AGCO Parts LHM Extra

Disclaimer

This information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process. Such information is, to the best of the company's knowledge and belief, accurate and reliable as of the date indicated. However, no warranty guarantee or representation is made to its accuracy, reliability or completeness. It is the user's responsibility to satisfy himself as to the suitability of such information for his own particular use.