



**MASSEY FERGUSON**

**SAFETY DATA SHEET**

**MF Ultra Engine Oil 15W-40 (CJ4)**

**SECTION 1: Identification of the substance/mixture and of the company/undertaking**

1.1. Product identifier

Product name MF Ultra Engine Oil 15W-40 (CJ4)  
 Product number 7403-203  
 Internal identification GHS21780  
 REACH registration number n/a Mixture

1.2. Relevant identified uses of the substance or mixture and uses advised against

Identified uses Engine oil.  
 Uses advised against Non specified unless otherwise stated within this MSDS

1.3. Details of the supplier of the safety data sheet

Supplier **Oil Distributors**  
 2a South Belt  
 Rangiora 7400  
 Ph: 0800 70 10 10  
 Fax: 03 313 6428  
[admin@oilistributors.co.nz](mailto:admin@oilistributors.co.nz)

Emergency telephone **National Poison Control Centre** 0800 764 766

**SECTION 2: Hazards identification**

2.1. Classification of the substance or mixture

Classification

Physical hazards Not Classified  
 Health hazards Elicitation - EUH208 Environmental hazards  
 Not Classified

Classification (67/548/EEC or 1999/45/EC) Not Classified

2.2. Label elements

## MF Ultra Engine Oil 15W-40 (CJ4)

Hazard statements	EUH208 Contains Calcium long chain alkaryl sulphonate. May produce an allergic reaction.
Precautionary statements	<p>P264 Wash contaminated skin thoroughly after handling.</p> <p>P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.</p> <p>P337+P313 If eye irritation persists: Get medical advice/attention.</p> <p>P501a Dispose of contents/container to hazardous or special waste collection point.</p>

### 2.3. Other hazards

\_\_\_\_\_

This product does not contain any substances classified as PBT or vPvB.

## SECTION 3: Composition/information on ingredients

### 3.2. Mixtures

Distillates,hydrotreated heavy paraffinic		60-100%
CAS number: 64742-54-7	EC number: 265-157-1	REACH registration number: 012119484627-25-0014
Classification Not Classified	Classification (67/548/EEC or 1999/45/EC) -	
Distillates, hydrotreated heavy paraffinic		5-10%
CAS number: 64742-54-7	EC number: 265-157-1	REACH registration number: 012119484627-25-0014
Classification Asp. Tox. 1 - H304	Classification (67/548/EEC or 1999/45/EC) -	
Lubricating oil (petroleum) C20-C50,hydrotreated,neutral oil- 5-10% based		
CAS number: 72623-87-1	EC number: 276-738-4	REACH registration number: 01- 2119474889-13-XXXX
Classification Not Classified	Classification (67/548/EEC or 1999/45/EC) -	
Polyolefin polyamine succinimide borated		1-5%
CAS number: —		
Classification Aquatic Chronic 4 - H413	Classification (67/548/EEC or 1999/45/EC) R53.	
Polyolefin polyamine succinimide		1-5%
CAS number: —		
Classification Aquatic Chronic 4 - H413	Classification (67/548/EEC or 1999/45/EC) R53.	

## MF Ultra Engine Oil 15W-40 (CJ4)

Phosphorodithioic acid, O,O-di-C1-14-alkyl esters, zinc salts	1-5%
CAS number: 68649-42-3	EC number: 272-028-3
	REACH registration number: 012119657973-23-XXXX
Classification Skin Irrit. 2 - H315 Eye Dam. 1 - H318 Aquatic Chronic 2 - H411	Classification (67/548/EEC or 1999/45/EC) Xi;R41. N;R51/53.
Polyolefin polyamine succinimide polyol	1-5%
CAS number: —	
Classification Aquatic Chronic 4 - H413	Classification (67/548/EEC or 1999/45/EC) R53.
Propylene Pentamer	<1%
CAS number: 15220-87-8	
Classification Asp. Tox. 1 - H304 Aquatic Chronic 2 - H411	Classification (67/548/EEC or 1999/45/EC) Xn;R65. Xi;R38. N;R51/53.

The Full Text for all R-Phrases and Hazard Statements are Displayed in Section 16.

Composition comments      If REACH registration numbers do not appear the substance is either exempt from registration, does not meet the minimum volume threshold for registration, the registration date has not yet come due or this information is proprietary.

### SECTION 4: First aid measures

#### 4.1. Description of first aid measures

General information	Get medical attention if any discomfort continues. May produce an allergic reaction.
Inhalation	If spray/mist has been inhaled, proceed as follows. Move affected person to fresh air and keep warm and at rest in a position comfortable for breathing. Get medical attention if any discomfort continues.
Ingestion	Get medical attention if any discomfort continues. Do not induce vomiting.
Skin contact	Remove contaminated clothing immediately and wash skin with soap and water.
Eye contact	Rinse immediately with plenty of water. Remove any contact lenses and open eyelids wide apart. Continue to rinse for at least 15 minutes. Get medical attention promptly if symptoms occur after washing.

#### 4.2. Most important symptoms and effects, both acute and delayed

General information	If aspiration into the lungs is suspected, eg when vomiting, admit to hospital immediately.
Inhalation	Upper respiratory irritation.
Ingestion	May cause discomfort if swallowed. The product contains mineral oil, which if aspirated into the lungs through vomiting after ingestion, may result in chemical pneumonia.
Skin contact	Prolonged contact may cause redness, irritation and dry skin.

## MF Ultra Engine Oil 15W-40 (CJ4)

Eye contact Irritation of eyes and mucous membranes.

4.3. Indication of any immediate medical attention and special treatment needed

---

Notes for the doctor Treat symptomatically.

### SECTION 5: Firefighting measures

5.1. Extinguishing media

---

Suitable extinguishing media Extinguish with foam, carbon dioxide, dry powder or water fog.

Unsuitable extinguishing media Do not use water jet as an extinguisher, as this will spread the fire.

5.2. Special hazards arising from the substance or mixture

Specific hazards Heat from fire could result in drums bursting

Hazardous combustion products Protection against nuisance dust must be used when the airborne concentration exceeds 10 mg/m<sup>3</sup>. Oxides of carbon. Oxides of nitrogen. Fire may also create other unidentified organic gases some of which may be toxic.

5.3. Advice for firefighters

Protective actions during firefighting Control run-off water by containing and keeping it out of sewers and watercourses.

Special protective equipment apparatus. for firefighters Wear self-contained breathing

### SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

---

Personal precautions For personal protection, see Section 8. In case of spills, beware of slippery floors and surfaces.

6.2. Environmental precautions

---

Environmental precautions Contain spillage with sand or earth. Avoid the spillage or runoff entering drains, sewers or watercourses. The product is insoluble in water and will spread on the water surface.

6.3. Methods and material for containment and cleaning up

---

Methods for cleaning up Contain spillage with sand or earth. Collect spillage for reclamation or disposal in sealed containers via a licensed waste contractor. Avoid water contacting spilled material or leaking containers. Spillages or uncontrolled discharges into watercourses must be reported immediately to the Environmental Agency or other appropriate regulatory body. In case of spillage on water prevent the spread by use of suitable barrier equipment

6.4. Reference to other sections

---

## MF Ultra Engine Oil 15W-40 (CJ4)

Reference to other sections For personal protection, see Section 8. See Section 11 for additional information on health hazards. For waste disposal, see section 13.

### SECTION 7: Handling and storage

#### 7.1. Precautions for safe handling

Usage precautions Avoid spilling. Always remove oil with soap and water or skin cleaning agent, never use organic solvents. Do not use oil-contaminated clothing or shoes, and do not put rags moistened with oil into pockets.

#### 7.2. Conditions for safe storage, including any incompatibilities

Storage precautions Store in tightly-closed, original container in a dry, cool and well-ventilated place.  
Storage class Miscellaneous hazardous material storage.

#### 7.3. Specific end use(s)

Specific end use(s) The identified uses for this product are detailed in Section 1.2.

### SECTION 8: Exposure Controls/personal protection

#### 8.1. Control parameters Occupational exposure limits

Distillates,hydrotreated heavy paraffinic

Long-term exposure limit (8-hour TWA): ACGIH 5 mg/m<sup>3</sup>

Short-term exposure limit (15-minute): ACGIH 10 mg/m<sup>3</sup>

Lubricating oil (petroleum) C20-C50,hydrotreated,neutral oil- based

Long-term exposure limit (8-hour TWA): ACGIH 5 mg/m<sup>3</sup>

Propylene Pentamer

Long-term exposure limit (8-hour TWA): WEL 4 mg/m<sup>3</sup>

ACGIH = American Conference of Governmental Industrial Hygienists.

WEL = Workplace Exposure Limit

Lubricating oil (petroleum) C20-C50,hydrotreated,neutral oil- based (CAS: 72623-87-1)

Ingredient comments Finnish HTP 5mg/m<sup>3</sup> 8 hr

#### 8.2. Exposure controls

##### Protective equipment



Appropriate engineering controls

Provide adequate general and local exhaust ventilation. Observe any occupational exposure limits for the product or ingredients.

Eye/face protection

Eyewear complying with an approved standard should be worn if a risk assessment indicates eye contact is possible. The following protection should be worn: Chemical splash goggles or face shield.

## MF Ultra Engine Oil 15W-40 (CJ4)

Hand protection	The most suitable glove should be chosen in consultation with the glove supplier/manufacturer, who can provide information about the breakthrough time of the glove material.
Other skin and body protection	Use barrier creams to prevent skin contact.
Hygiene measures	Use engineering controls to reduce air contamination to permissible exposure level. Wash promptly with soap and water if skin becomes contaminated.
Respiratory protection	No specific recommendations. Respiratory protection must be used if the airborne contamination exceeds the recommended occupational exposure limit.
Thermal hazards	Not anticipated under normal conditions of use. The product is combustible if heated excessively and an ignition source is applied.
Environmental exposure controls	Do not allow product to contaminate land.

### SECTION 9: Physical and Chemical Properties

#### 9.1. Information on basic physical and chemical properties

Appearance	Liquid.
Colour	Amber.
Odour	Characteristic. Oil-like.
Odour threshold	Not known.
pH	Not applicable.
Melting point	-34°C Pour point
Initial boiling point and range	>320°C @ 101.3 kPa
Flash point	208°C PMCC (Pensky-Martens closed cup).
Evaporation rate	Not relevant.
Upper/lower flammability or explosive limits	Not known.
Other flammability	Product is not flammable but on excessive heating may become combustible.
Vapour pressure	<0.1 kPa @ 20°C
Vapour density	Not determined.
Relative density	0.877 @ 15.6°C
Solubility(ies)	Insoluble in water. Soluble in the following materials: Organic solvents.
Partition coefficient	Not determined. log Kow: > 7 This figure is typical of mineral oil.
Auto-ignition temperature	No specific test data are available.
Decomposition Temperature	Not determined.
Viscosity	104.7 cSt @ 40°C
Explosive properties	Not considered to be explosive.

## MF Ultra Engine Oil 15W-40 (CJ4)

Explosive under the influence of a flame Not considered to be explosive.

Oxidising properties The mixture itself has not been tested but none of the ingredient substances meet the criteria for classification as oxidising.

### 9.2. Other information

Volatile organic compound The product is a complex mixture, the majority of which would not be classed as a VOC. However it cannot be discounted that trace or low levels of VOC's may be present.

## SECTION 10: Stability and reactivity

### 10.1. Reactivity

---

Reactivity There are no known reactivity hazards associated with this product.

### 10.2. Chemical stability

---

Stability Stable at normal ambient temperatures and when used as recommended.

### 10.3. Possibility of hazardous reactions

---

Possibility of hazardous reactions Unlikely to occur under normal conditions of use. Unlikely to occur.

### 10.4. Conditions to avoid

---

Conditions to avoid Avoid heat, flames and other sources of ignition.

### 10.5. Incompatible materials

---

Materials to avoid Strong oxidising agents.

### 10.6. Hazardous decomposition products

---

Hazardous decomposition products Oxides of carbon. Oxides of nitrogen.

## SECTION 11: Toxicological information

### 11.1. Information on toxicological effects Acute toxicity - oral

Notes (oral LD<sub>50</sub>) Not expected to be highly toxic based on information of ingredients. Based on available data the classification criteria are not met.

### Acute toxicity - dermal

Notes (dermal LD<sub>50</sub>) Not expected to be highly toxic based on information of ingredients. Based on available data the classification criteria are not met.

### Acute toxicity - inhalation

Notes (inhalation LC<sub>50</sub>) Not determined. The product is unlikely to present any significant inhalation hazard at ambient temperatures and under normal conditions of use.

### Serious eye damage/irritation

Serious eye damage/irritation May cause mild, short lasting discomfort to eyes.

### Respiratory sensitisation

## MF Ultra Engine Oil 15W-40 (CJ4)

Respiratory sensitisation	No evidence to suggest the product will be a respiratory sensitiser. Repeated exposure to oil mists may cause respiratory damage.
<u>Skin sensitisation</u>	
Skin sensitisation	Not expected to be a skin sensitizer based on information on components.
<u>Carcinogenicity</u>	
Carcinogenicity	This product contains mineral oils which are considered to be severely refined and not considered to be carcinogenic under IARC. All of the oils in this product have been demonstrated to contain less than 3% extractables by the IP346 test
<u>Reproductive toxicity</u>	
Reproductive toxicity - fertility	No data available to suggest the product will cause reproductive toxicity.
<u>Specific target organ toxicity - single exposure</u>	
STOT - single exposure	Based on available data the classification criteria are not met.
<u>Specific target organ toxicity - repeated exposure</u>	
STOT - repeated exposure	Based on available data the classification criteria are not met.
<u>Aspiration hazard</u>	
Aspiration hazard	Kinematic viscosity > 20.5 mm <sup>2</sup> /s. The product viscosity is greater than the upper limit assigned for classification. Although not classified, the product contains mineral oil. If aspirated into the lungs e.g. through vomiting after ingestion, admit to hospital immediately.
General information	This product has low toxicity. Only large quantities are likely to have adverse effects on human health.
Inhalation	Unlikely to be hazardous by inhalation because of the low vapour pressure of the product at ambient temperature.
Ingestion	No harmful effects expected from quantities likely to be ingested by accident.
Skin contact	Skin irritation should not occur when used as recommended. Repeated exposure may cause skin dryness or cracking.
Eye contact	May cause temporary eye irritation.
Acute and chronic health	Prolonged or repeated contact with used oil may cause serious skin diseases, such as hazards dermatitis and skin cancer.



## MF Ultra Engine Oil 15W-40 (CJ4)

### SECTION 12: Ecological Information

Ecotoxicity	Based on available data the classification criteria are not met. Not regarded as dangerous for the environment.
12.1. Toxicity	
<hr/>	
Toxicity	Based on available data the classification criteria are not met. Not considered toxic to fish.
Acute toxicity - aquatic invertebrates	Based on available data the classification criteria are not met.
12.2. Persistence and degradability	
Persistence and degradability	The product contains mineral oil which has limited biodegradability in CEC test methods but will biodegrade slowly in aerobic water and sediments and is considered ultimately biodegradable.
Stability (hydrolysis)	The product is based on highly refined mineral oils that are considered stable to hydrolysis.
Biodegradation	The product is not considered readily biodegradeable, albeit the major constituents are expected to ultimately biodegrade.
Biological oxygen demand	Not determined.
Chemical oxygen demand	Not determined.
12.3. Bioaccumulative potential	
Bioaccumulative potential	Bioaccumulation is unlikely to be significant because of the low water-solubility of this product.
Partition coefficient	Not determined. log Kow: > 7 This figure is typical of mineral oil.
12.4. Mobility in soil	
Mobility	The product is non-volatile. The product is insoluble in water and will spread on the water surface.
Henry's law constant	Not determined.
12.5. Results of PBT and vPvB assessment	
Results of PBT and vPvB assessment	This product does not contain any substances classified as PBT or vPvB.
12.6. Other adverse effects	
<hr/>	
Other adverse effects	None known.

### SECTION 13: Disposal considerations

#### 13.1. Waste treatment methods

General information	This material and its container must be disposed of as hazardous waste. Dispose of waste via a licensed waste disposal contractor.
---------------------	--



## MF Ultra Engine Oil 15W-40 (CJ4)

Control of Substances Hazardous to Health Regulations 2002 (as amended). The Carriage of Dangerous Goods and Use of Transportable Pressure Equipment Regulations 2009 (SI 2009 No. 1348) (as amended) ["CDG 2009"].

EU legislation	Dangerous Preparations Directive 1999/45/EC. Dangerous Substances Directive 67/548/EEC. Regulation (EC) No 1907/2006 of the European Parliament and of the Council of 18 December 2006 concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals (REACH) (as amended). Regulation (EC) No 1272/2008 of the European Parliament and of the Council of 16 December 2008 on classification, labelling and packaging of substances and mixtures (as amended).
Guidance	Workplace Exposure Limits EH40. Safety Data Sheets for Substances and Preparations.

### 15.2. Chemical safety assessment

No chemical safety assessment has been carried out.

#### Inventories

##### Canada - DSL/NDSL

All the ingredients are listed or exempt.

##### US - TSCA

All the ingredients are listed or exempt.

##### Australia - AICS

All the ingredients are listed or exempt.

##### Korea - KECI

All the ingredients are listed or exempt.

##### China - IECSC

All the ingredients are listed or exempt.

##### Philippines – PICCS

All the ingredients are listed or exempt.

##### New Zealand - NZIOC

All the ingredients are listed or exempt.

**ERMA Approval Code:** HSR002606

#### SECTION 16: Other information

Revision comments	NOTE: Lines within the margin indicate significant changes from the previous revision.
Issued by	Regulatory Affairs
Revision date	26/11/2015
Revision	2

## MF Ultra Engine Oil 15W-40 (CJ4)

Supersedes date	20/11/2015
SDS number	21780
Hazard statements in full	<p>EUH208 Contains Calcium long chain alkaryl sulphonate. May produce an allergic reaction. H304 May be fatal if swallowed and enters airways.</p> <p>H315 Causes skin irritation.</p> <p>H318 Causes serious eye damage.</p> <p>H411 Toxic to aquatic life with long lasting effects.</p> <p>H413 May cause long lasting harmful effects to aquatic life.</p>

This information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process. Such information is, to the best of the company's knowledge and belief, accurate and reliable as of the date indicated. However, no warranty, guarantee or representation is made to its accuracy, reliability or completeness. It is the user's responsibility to satisfy himself as to the suitability of such information for his own particular use.