

# VALTRANS TRANSMISSION XT60

## Special Oil for Valtra Tractor Transmissions

### Description

Valtra Transmission XT60 is a transmission oil, specially developed for new demanding CVT transmissions. Transmission XT60 is also recommended for many other tractor transmissions, e.g. to all present Valtra models, too.

Due to high viscosity index and extreme shear stability, it is recommended for use all the year round, in all climate conditions. Its additive package has been developed for HD transmissions, which have electro-hydraulic controls and wet brakes. Load carrying capacity exceeds the API GL-4 requirements.

The balanced base oil-additive combination effectively resists wear, foaming and oxidation enabling maximum oil performance and maximum oil change periods even in extremely heavy use.

### Applications

Valtra Transmission XT60 is ideal for all Valtra tractors transmissions and hydraulic systems. The exceptions are final drives with separate oil space and front axles. Both of these compartments require products with an API GL5 performance level.

### Performance Levels

Valtra G2-08

API GL-4

### Physical Characteristics

Density @ 15 °C (kg/dm <sup>3</sup> )	0,877
Flash point (°C)	204
Viscosity @ 40 °C (cSt)	60.1
Viscosity @ 100 °C (cSt)	9.4
Viscosity index (VI)	140
Pour point (°C)	-42

Universal tractor oils fail to meet this requirement and therefore do not meet the specification claimed.

### Technical Properties

CEC L-45-A-99 test (KRL 20hr) >8.0 cSt @ 100C (after test)

### Safety Precautions

No specific danger under normal conditions. Continuous skin contact must be avoided.  
Dispose of used oil into an authorised used oil collection point.

### Part numbers:

VACC3407 25 litres  
VACC3408 205 litres  
VACC3409 1000 litres IBC

Date Created: 1/7/2009 Ref VA/VTXT Page 1 of 1